


Butyl Tape Sealant

SF 900: An inert, tape applied, water and air sealant

Featuring

- Permanently flexible seal Will not dry out or become brittle in service
- Easy and quick to use Provides an immediate seal, without using special equipment
- Good adhesion to most substrates Seals most common building surfaces
- Solvent Free Safe to use, no fumes or special precautions
- Excellent UV & ageing resistance Durable & long lasting seal
- High resistance to flow Wide service temperature range
- High Joint Movement Capability High resistance to pumping and internal rupturing

Typical Applications include:



Application

Optimum performance will be achieved when applied to clean, dry, dust and grease free surfaces. The tape should be applied firmly to one surface, the release paper removed and the closing surface applied with pressure to maximise the pressure sensitive nature of this sealant. The joint should be compressed by 20% for optimum performance. Best applied at temperatures above 4°C.

Performance

- **Life Expectancy** In excess of 20 years when used in a properly constructed joint and in accordance with manufacturers directions
- **Shelf Life** 1 year in ambient conditions
- **Recommended Service Temperature** -40 to +90°C
- **Chemical Resistance**

Dilute acids and alkali:	Good
Detergents:	Good
Petroleum based solvents:	Will dissolve exposed sealant
- **Joint Movement Capability** 15%
- **Flow** Tested @ 80°C - less than 5mm flow (50g coupon test)
- **Toxicity** Contains no known toxic ingredients, solvent free

Product Specification

- **Colour** Grey, off white, black, teak or bespoke.
- **Formulation** Polybutene and inert fillers with an elastomeric backbone formed into an homogeneous tape carried on a release paper
- **Sizes**

A variety of profiles is available:	
Thickness 1mm to 15mm –	tolerance $\pm 10\%$
Widths up to 25mm –	tolerance $\pm 1\text{mm}$
Widths over 25mm to 100mm -	tolerance $\pm 2\text{mm}$
Widths over 100mm –	tolerance $\pm 3\text{mm}$
Industry standard and bespoke roll lengths available	

Sealflex SF 900

Just one of a comprehensive selection of high performance sealant and bonding tapes for sealing, jointing and acoustic applications.

The information provided herein is true and accurate at the time of publication and based on current data. It is recommended that customers evaluate the product under the conditions of their intended usage. Goods are supplied according to our standard terms and conditions, available on request.

SEALFLEX LIMITED

Florence Road Business Park Kelly Bray Callington Cornwall
 PL17 8EX England
Tel 01579 383333
Fax 01579 384040
Email: sales@sealflex.co.uk
Website: www.sealflex.co.uk
 Registered in England No. 2259604
 Registered office: Kelly Bray



SF 900