



SF 908

High Performance Butyl Tape

SF 908: An inert, tape applied, water and air sealant based on cross linked butyl rubber.

1 of 2

Featuring:

- Aggressive Tack Quick 'grab' even at lower temperatures
- Good adhesion to most surfaces Includes polyethylene, polypropylene UPVC Hypalon®
- High movement capability Suitable for most joint applications
- Excellent UV and ageing resistance Durable and long lasting seal
- High shear strength Tough elastic seal
- High peel strength Bonds tenaciously
- Solvent Free Safe to use, no fumes or special precautions required

Performance

- Life Expectancy In excess of 20 years when used in a properly constructed joint and in accordance with manufacturers directions
- Shelf Life 1 year in ambient conditions
- Recommended Service Temperature -40 to +90°C
- Chemical Resistance
 - Dilute acids and alkali: Good
 - Detergents: Good
 - Petroleum based solvents: Will dissolve exposed sealant
- Joint Movement Capability 25%
- Typical test results observed at 20°C
 - Tensile adhesion 1.64 Kg/cm²
 - Shear adhesion 2.0 Kg/cm²
 - Elongation > 350% @ 300mm/min
- Toxicity Contains no known toxic ingredients, solvent free

Product Specification

- **Colour** Black, off white or bespoke
- **Formulation** Polybutene and inert fillers with an elastomeric backbone formed into an homogeneous tape carried on a release paper
- **Sizes** A variety of profiles is available:

Thickness 1mm to 15mm –	tolerance $\pm 10\%$
Widths up to 25mm –	tolerance $\pm 1\text{mm}$
Widths over 25mm to 100mm –	tolerance $\pm 2\text{mm}$
Widths over 100mm –	tolerance $\pm 3\text{mm}$
Industry standard and bespoke roll lengths available	

Application

Optimum performance will be achieved when applied to clean, dry, dust and grease free surfaces. The tape should be applied firmly to one surface, the release paper removed and the closing surface applied with pressure to maximise the pressure sensitive nature of this sealant. The joint should be compressed by 20% for optimum performance. Best applied at temperatures above 4°C.

Typical Applications include:

- **Roofing and Cladding** Edge and side laps of sheeting (including aluminium), sealing between upstands and sheet on butyl and Hypalon® roofing membranes.
- **Construction** Ideal where a high joint movement sealant would be selected. Useful for bonding polythene and damp proof membranes.
- **Domestic** PVC extrusions to ceramic in bath, shower and kitchen applications.

Sealflex SF 908

Just one of a comprehensive selection of high performance sealant and bonding tapes for sealing, jointing and acoustic applications.

The information provided herein is true and accurate at the time of publication and based on current data. It is recommended that customers evaluate the product under the conditions of their intended usage. Goods are supplied according to our standard terms and conditions, available on request.

SEALFLEX LIMITED

Florence Road Business Park Kelly Bray Callington Cornwall
 PL17 8EX England
Tel 01579 383333
Fax 01579 384040
Email: sales@sealflex.co.uk
Website: www.sealflex.co.uk
 Registered in England No. 2259604
 Registered office: Kelly Bray


 The logo for Sealflex SF 908 is a blue trapezoidal shape with a white border. The text 'SF 908' is written in a bold, white, sans-serif font inside the shape.

SF 908